By Appointment to
Her Majesty the Queen
Water Treatment Services
Aquadition Limited
Portsmouth

WATER TREATMENT
AQUADITION

Aquadition Limited
220 Copnor Road,
Portsmouth,
Hants, PO3 5DA

T: 023 9269 1035
F: 023 9261 8200
W: www.aquadition.co.uk
E: sales@aquadition.co.uk

ENVIROSOFT WATER SOFTENER

TECHNICAL SPECIFICATION

Connections

Inlet / Outlet	¾" BSP (male)
Drain	3/8" push fit
Overflow	½" hose spigot

Operating Conditions

Maximum working temperature	20° C
Minimum working temperature	Protect from freezing
Maximum operating pressure	8 bar (6 bar daytime)
Minimum operating pressure	1 bar dynamic

Overall Dimensions

Height	490 mm	(19 ¼")
Depth	445 mm	(17 ½")
Width	206 mm	(8 ¼")
Width (with connections)	267 mm	(10 ¼")

Softener Details

Resin Volume (monosphere beads 0.35mm)	2 x 4.3 litres resin per tank
Resin tank dimensions	140mm diameter by 400 mm high
Salt storage capacity	2 x 4kg block salt
Shipping Weight	20 kg

Overall Data

Maximum flow rate	55 L/min
Salt used per regeneration	300 grams
Regeneration time	10 mins
Water used per regeneration	17 litres

PLEASE NOTE - CONNECTIONS CAN BE ON THE LEFT OR RIGHT

Installation Cost - Subject to Site Survey