



## Aquadition Simplex Water Softeners

Automatic Time Controlled

&

Electronic Meter Controlled

### Specification Data:

Model	ASC-10TC	ASCM-10M	ASC-15TC	ASCM-15M
Height	530mm (21")	530mm (21")	665mm (26.2")	665mm (26.2")
Width	275mm (11")	275mm (11")	275mm (11")	275mm (11")
Depth	460mm (18.1")	460mm (18.1")	460mm (18.1")	460mm (18.1")
Volume of Softened Water @ 20°C Clarke (3000 ppm)	1667 litres (366 gallons)	1667 litres (366 gallons)	2500 litres (550 gallons)	2500 litres (550 gallons)
Resin Volume	10 Litres	10 Litres	15 Litres	15 Litres
Maximum working pressure	120 psi	120 psi)	120 psi	120 psi)
Minimum working pressure	20 psi	20 psi	20 psi	20 psi
Salt used per regeneration	1.5kg	1.5kg	2.2 kg	2.2kg
Inlet and outlet connections	¾" BSP female	¾" BSP female	¾" BSP female	¾" BSP female
Drain connection	½" BSP female	½" BSP female	½" BSP female	½" BSP female
Overflow	½" hose spigot	½" hose spigot	½" hose spigot	½" hose spigot
Electrical	240 Volt 50 HZ	240 Volt 50 HZ	240 Volt 50 HZ	240 Volt 50 HZ
Price excluding VAT	<b>£538.00</b>	<b>£638.00</b>	<b>£600.00</b>	<b>£672.00</b>
VAT @ 20%	<b>£107.60</b>	<b>£127.60</b>	<b>£120.00</b>	<b>£134.40</b>
Total Cost	<b>£645.60</b>	<b>£765.60</b>	<b>£720.00</b>	<b>£806.40</b>

#### Automatic Time Controlled Water Softeners (TC)

- ◆ Time controlled water softeners regenerate after a fixed-time period. The regeneration days are set by the user, depending on water usage.

#### Automatic Meter Controlled Water Softeners (M)

- ◆ Smart memory monitors household water usage and programs itself accordingly, ensuring that softened water is always available on demand.

***Installation Cost - Subject to Site Survey.***

**Managing Director: Mr. J. R. Spry, Company Secretary: Mrs. J.E. Bawn**  
**VAT No. GB 803 5532 54**

Rev. 16(Sept 23)